

## 3400 SERIES GENERAL

### INFORMATION PAGE

3400 Series - General



## SPECIFICATIONS

### Applications

- Commercial
- Industrial
- Institution

### Backsets

- 2-3/4" (70 mm) - standard
- 2-3/8" (60 mm) - optional
- 3-3/4" (94 mm) - optional
- 5" (128 mm) - optional

### Certifications

- BHMA Certified ANSI A156.2, Series 4000, Grade 1
- ADA Compliant ANSI A117.1 Accessibility Code
- ANSI A250.13 Severe Windstorm Resistant Component
- UL/cUL Listed for all functions up to 3 hours for "A" label single doors (for double door application, UL/cUL Listed when used with 3/4" latchbolt)
- UL10C Positive Pressure Rated
- UL10B Neutral Pressure Rated
- Miami-Dade County, Florida NOA #22-0816.08, Exp. Aug. 16, 2027. Must specify.

### Cylinders/Cores

- Brass 6-pin, keyed different - Schlage C Keyway - standard
- Cylinder drilled 6 pin, Keyed 5 pin - standard
- Other keying options, including keyed 6-pin, available from factory
- Zero bit cylinders will be 6 pin - standard
- SFIC uncombined or combined, brass 6- or 7-pin sold separately
- Large Format Interchangeable Core option available
- LFIC zero bitted or combined, brass 6-pin sold separately - Schlage C keyway only

### Door Thickness

1-3/8" - 2" (35 mm - 51 mm)

### Exposed Trim

- Lever: Cast zinc
- Rose: Wrought brass or stainless steel
- Intruder Classroom function has locking indicator arrow stamped on the interior rose

### Features

- No exposed mounting screws
- Non-handed
- Free wheeling levers

### Finishes

- US3, US4, US10B, US26, US26D and BLK
- Anti-Microbial Coating (US26D finish only)

<b>Functions</b>	<ul style="list-style-type: none"> <li>• <a href="#">10 - Passage</a></li> <li>• <a href="#">17 - Dummy</a></li> <li>• <a href="#">40 - Privacy</a></li> <li>• <a href="#">50 - Office</a></li> <li>• <a href="#">53 - Entry</a></li> <li>• <a href="#">70 - Classroom</a></li> <li>• <a href="#">73 - Corridor</a></li> <li>• <a href="#">80 - Storeroom</a></li> <li>• <a href="#">82 - Institution</a></li> <li>• <a href="#">95 - Intruder Classroom</a></li> </ul>
<b>Installation</b>	<ul style="list-style-type: none"> <li>• Comes pre-set for 1-3/4" thick doors for quicker installation</li> <li>• Threaded mounting bracket adjusts to proper door thickness in seconds</li> <li>• Only two screws needed to fully secure inside and outside assemblies to the door</li> <li>• Screws will ratchet tight letting installer know the lockset is properly tightened</li> <li>• Roses and levers snap on in seconds</li> </ul>
<b>Keys</b>	Two operating keys supplied per lock
<b>Latchbolt Type</b>	<ul style="list-style-type: none"> <li>• 1/2" (13 mm) throw, stainless steel</li> <li>• 1-1/8" x 2-1/4" (29 mm x 57 mm) faceplate</li> <li>• Deadlocking latchbolt prevents manipulation when door is closed; keyed functions only</li> <li>• Square corner faceplates standard, round corner available</li> <li>• 3/4" (19 mm) latch available</li> </ul>
<b>Lever Options</b>	Archer, August, Withnell
<b>Lock Chassis</b>	<ul style="list-style-type: none"> <li>• Heavy gauge steel, zinc dichromated for corrosion resistance</li> <li>• Free wheeling levers</li> <li>• Thru-bolt mounting levers</li> </ul>
<b>Notes</b>	<ul style="list-style-type: none"> <li>• 2-1/8" (54 mm) diameter with thru-bolt holes (cross bore)</li> <li>• Latch hole - 1" (25 mm) diameter (edge bore)</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>• Lead lined</li> <li>• Tactile knurling</li> <li>• Split finish</li> <li>• Additional latchbolts and strikes available</li> </ul>
<b>Rose Diameter</b>	3-17/32" (90 mm) levers; 3" (76 mm) knobs
<b>Strikes</b>	<ul style="list-style-type: none"> <li>• 3935 ASA 1-1/4" x 4-7/8" (32 mm x 124 mm) strike - Standard</li> <li>• 3933 T-Strike - Optional</li> <li>• 3934 Full Lip Strike - Optional</li> <li>• 3958 - Full Lip Strike, Round Corner - Optional</li> </ul>
<b>Warranty</b>	Lifetime Warranty