

## 3810E - PASSAGE - F01

3810E



BHMA



cUL US LISTED



## SPECIFICATIONS

<b>Applications</b>	<ul style="list-style-type: none"> <li>• Heavy Duty Commercial</li> <li>• Industrial</li> <li>• Institutional</li> </ul>
<b>Backsets</b>	2-3/4" (70mm)
<b>Certifications</b>	<ul style="list-style-type: none"> <li>• ADA Compliant ANSI A117.1 Accessibility Code</li> <li>• UL/cUL Listed for all functions up to 3 hours "A" label single doors</li> <li>• UL10C Positive Pressure Rated</li> <li>• BHMA Certified ANSI A156.13, Series 1000, Grade 1</li> </ul>
<b>CTC Length</b>	3-5/8" (92mm)
<b>Door Thickness</b>	<ul style="list-style-type: none"> <li>• 1-3/4" - 2-1/2" (45 mm - 64 mm)</li> <li>• Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep</li> </ul>
<b>Escutcheons</b>	1-15/16" x 8" (50 mm x 203 mm)
<b>Exposed Trim</b>	<ul style="list-style-type: none"> <li>• Cast Zinc - Standard</li> <li>• Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only</li> </ul>
<b>Finishes</b>	<ul style="list-style-type: none"> <li>• US3, US4, US10B, US26, US26D, US32D*</li> <li>• *US32D look on a cast zinc lever</li> <li>• Withnell and William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order.</li> <li>• US3, US4 and US26 subject to extended lead time</li> </ul>
<b>Functions</b>	Passage (F01)
<b>Latchbolt Type</b>	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
<b>Lever Options</b>	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William, and Withnell
<b>Lock Chassis</b>	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
<b>Notes</b>	<ul style="list-style-type: none"> <li>• No exposed mounting screws</li> <li>• Concealed thru-bolts</li> <li>• Body is easily field reversible (shipped LHR by default)</li> <li>• Self adjusting case for beveled doors</li> </ul>
<b>Options</b>	<ul style="list-style-type: none"> <li>• Tactile Warning</li> </ul>

- Lead Lining
- Split Finish
- Factory Handing Available (if specified)
- Request to Exit (RX)

**Strikes**

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

**Warranty**

Lifetime