

3810S - PASSAGE - F01

3810S



BHMA



SPECIFICATIONS

Applications

- Heavy Duty Commercial
- Industrial
- Institutional

Backsets

2-3/4" (70mm)

Certifications

- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours "A" label single doors
- UL10C Positive Pressure Rated
- BHMA Certified ANSI A156.13, Series 1000, Grade 1

CTC Length

3-5/8" (92mm)

Door Thickness

- 1-3/4" - 2-1/2" (45 mm - 64 mm)
- Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep

Exposed Trim

- Cast Zinc - Standard
- Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only

Finishes

- US3, US4, US10B, US26, US26D, US32D*
- *US32D look on a cast zinc lever
- Withnell and William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order.
- US3, US4 and US26 subject to extended lead time

Functions

Passage (F01)

Latchbolt Type

3/4" (19 mm) throw with anti-friction tongue, all stainless steel

Lever Options

Archer, August, Charles, Johnston, Joshua, Louis, Warren, William, and Withnell

Lock Chassis

4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)

Notes

- No exposed mounting screws
- Concealed thru-bolts
- Body is easily field reversible (shipped LHR by default)
- Self adjusting case for beveled doors

Options

- Tactile Warning
- Lead Lining

- Split Finish
- Factory Handing Available (if specified)
- Request to Exit (RX)

Rose Diameter

2-7/16" (62mm)

Strikes

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

Warranty

Lifetime