

3844E - PRIVACY W/ COINTURN

(F22)

3844E



BHMA

LIFETIME WARRANTY

UL LISTED



SPECIFICATIONS

| | |
|-----------------------|---|
| Applications | <ul style="list-style-type: none"> • Heavy Duty Commercial • Industrial • Institutional |
| Backsets | 2-3/4" (70mm) |
| Certifications | <ul style="list-style-type: none"> • ADA Compliant ANSI A117.1 Accessibility Code • UL/cUL Listed for all functions up to 3 hours "A" label single doors • UL10C Positive Pressure Rated • BHMA Certified ANSI A156.13, Series 1000, Grade 1 |
| CTC Length | 3-5/8" (92mm) |
| Door Thickness | <ul style="list-style-type: none"> • 1-3/4" - 2" (45 mm - 51 mm) • Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep |
| Escutcheons | 1-15/16" x 8" (50 mm x 203 mm) |
| Exposed Trim | <ul style="list-style-type: none"> • Cast Zinc - Standard • Cast Stainless Steel - Optional for Withnell (WTS) or William (WLS) only |
| Finishes | <ul style="list-style-type: none"> • US3, US4, US10B, US26, US26D, US32D* • *US32D look on a cast zinc lever • Withnell and William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order. • US3, US4 and US26 subject to extended lead time |
| Functions | Privacy w/ Cointurn (F22) |
| Latchbolt Type | 3/4" (19 mm) throw with anti-friction tongue, all stainless steel |
| Lever Options | Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell |
| Lock Chassis | 4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm) |
| Notes | <ul style="list-style-type: none"> • No exposed mounting screws • Concealed thru-bolts • Body is easily field reversible (shipped LHR by default) • Self adjusting case for beveled doors |
| Options | <ul style="list-style-type: none"> • Tactile Warning |

- Lead Lining
- Split Finish
- Factory Handing Available (if specified)

Strikes

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

Warranty

Lifetime