

3850S - OFFICE

3850S



SPECIFICATIONS

Applications	<ul style="list-style-type: none">• Heavy Duty Commercial• Industrial• Institutional
Backsets	2-3/4" (70mm)
Certifications	<ul style="list-style-type: none">• ADA Compliant ANSI A117.1 Accessibility Code• UL/cUL Listed for all functions up to 3 hours "A" label single doors• UL10C Positive Pressure Rated• BHMA Certified ANSI A156.13, Series 1000, Grade 1
CTC Length	3-5/8" (92mm)
Cylinders/Cores	<ul style="list-style-type: none">• Brass - keyed different - Schlage C keyway - standard• Drilled 6-Pin, Keyed 5-Pin - standard• Other keying options, including keyed 6-pin, available from factory• Zero bit cylinders will be 6 pin keyed - standard• SFIC mortise housings available• SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard• LFIC mortise housings available• LFIC zero bitted or combined, brass 6-pin sold separately - standard. Schlage C keyway only.• Schlage "L" cam is used standard on Hager mortise locks
Door Thickness	<ul style="list-style-type: none">• 1-3/4" - 2-1/2" (45 mm - 64 mm)• Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep
Exposed Trim	<ul style="list-style-type: none">• Cast Zinc - Standard• Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only
Finishes	<ul style="list-style-type: none">• US3, US4, US10B, US26, US26D, US32D*• *US32D look on a cast zinc lever• Withnell and William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order• US3, US4 and US26 subject to extended lead time
Functions	Office
Keyway	Schlage C - Standard, other keyways optional

Latchbolt Type	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
Lever Options	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
Lock Chassis	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
Notes	<ul style="list-style-type: none">• No exposed mounting screws• Concealed thru-bolts• Body is easily field reversible (shipped LHR by default)• Self adjusting case for beveled doors
Options	<ul style="list-style-type: none">• Tactile Warning• Lead Lining• Split Finish• Factory Handing Available (if specified)• ADA Thumbturn• Request to Exit (RX)
Rose Diameter	2-7/16" (62mm)
Strikes	<ul style="list-style-type: none">• 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike• Optional strikes available
Warranty	Lifetime