

3853S - ENTRANCE - F20

3853S

**SPECIFICATIONS****Applications**

- Heavy Duty Commercial
- Industrial
- Institutional

Backsets

2-3/4" (70mm)

Certifications

- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours "A" label single doors
- UL10C Positive Pressure Rated
- BHMA Certified ANSI A156.13, Series 1000, Grade 1
- ANSI A250.13 Severe Windstorm Compliant (Must specify on PO)

CTC Length

3-5/8" (92mm)

Cylinders/Cores

- Brass - keyed different - Schlage C keyway - standard
- Drilled 6-Pin, Keyed 5-Pin - standard
- Other keying options, including keyed 6-pin, available from factory
- Zero bit cylinders will be 6 pin keyed - standard
- SFIC mortise housings available
- SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard
- LFIC mortise housings available
- LFIC zero bitted or combined, brass 6-pin sold separately - standard. Schlage C keyway only.
- Schlage "L" cam is used standard on Hager mortise locks

Deadbolt

1" (25 mm) throw - stainless steel

Door Thickness

- 1-3/4" - 2-1/2" (45 mm - 64 mm)
- Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep

Exposed Trim

- Cast Zinc - Standard
- Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only

Finishes

- US3, US4, US10B, US26, US26D, US32D*
- *US32D look on a cast zinc lever
- Withnell or William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order.
- US3, US4 and US26 subject to extended lead time

Functions	Entry (F20)
Keyway	Schlage C - Standard, other keyways optional
Latchbolt Type	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
Lever Options	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
Lock Chassis	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
Notes	<ul style="list-style-type: none">• No exposed mounting screws• Concealed thru-bolts• Body is easily field reversible (shipped LHR by default)• Self adjusting case for beveled doors
Options	<ul style="list-style-type: none">• Tactile Warning• Lead Lining• Split Finish• Factory Handing Available (if specified)• ADA Thumbturn
Rose Diameter	2-7/16" (62mm)
Strikes	<ul style="list-style-type: none">• 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike• Optional strikes available
Warranty	Lifetime