

## 3861E - APARTMENT ENTRANCE

(F09)

3861E



BHMA

LIFETIME  
WARRANTY

cUL US  
LISTED



## SPECIFICATIONS

### Applications

- Heavy Duty Commercial
- Industrial
- Institutional

### Backsets

2-3/4" (70mm)

### Certifications

- ADA Compliant ANSI A117.1 Accessibility Code
- UL/cUL Listed for all functions up to 3 hours "A" label single doors
- UL10C Positive Pressure Rated
- BHMA Certified ANSI A156.13, Series 1000, Grade 1

### CTC Length

3-5/8" (92mm)

### Cylinders/Cores

- Brass - keyed different - Schlage C keyway - standard
- Drilled 6-Pin, Keyed 5-Pin - standard
- Other keying options, including keyed 6-pin, available from factory
- Zero bit cylinders will be 6 pin keyed - standard
- SFIC mortise housings available
- SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard
- LFIC mortise housings available
- LFIC zero bitted or combined, brass 6-pin sold separately - standard. Schlage C keyway only.
- Schlage "L" cam is used standard on Hager mortise locks

### Door Thickness

- 1-3/4" - 2-1/2" (45 mm - 64 mm)
- Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep

### Escutcheons

1-15/16" x 8" (50 mm x 203 mm)

### Exposed Trim

- Cast Zinc - Standard
- Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only

### Finishes

- US3, US4, US10B, US26, US26D, US32D\*
- \*US32D look on a cast zinc lever
- Withnell and William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order.
- US3, US4 and US26 subject to extended lead time

### Functions

Apartment Entrance (F09)

<b>Keyway</b>	Schlage C - Standard, other keyways optional
<b>Latchbolt Type</b>	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
<b>Lever Options</b>	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
<b>Lock Chassis</b>	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
<b>Notes</b>	<ul style="list-style-type: none"><li>• No exposed mounting screws</li><li>• Concealed thru-bolts</li><li>• Body is easily field reversible (shipped LHR by default)</li><li>• Self adjusting case for beveled doors</li></ul>
<b>Options</b>	<ul style="list-style-type: none"><li>• Tactile Warning</li><li>• Lead Lining</li><li>• Split Finish</li><li>• Factory Handing Available (if specified)</li></ul>
<b>Strikes</b>	<ul style="list-style-type: none"><li>• 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike</li><li>• Optional strikes available</li></ul>
<b>Warranty</b>	Lifetime