

## 3880E - STOREROOM - F07

3880E



### SPECIFICATIONS

<b>Applications</b>	<ul style="list-style-type: none"> <li>• Heavy Duty Commercial</li> <li>• Industrial</li> <li>• Institutional</li> </ul>
<b>Backsets</b>	2-3/4" (70mm)
<b>Certifications</b>	<ul style="list-style-type: none"> <li>• ADA Compliant ANSI A117.1 Accessibility Code</li> <li>• UL/cUL Listed for all functions up to 3 hours "A" label single doors</li> <li>• UL10C Positive Pressure Rated</li> <li>• BHMA Certified ANSI A156.13, Series 1000, Grade 1</li> </ul>
<b>CTC Length</b>	3-5/8" (92mm)
<b>Cylinders/Cores</b>	<ul style="list-style-type: none"> <li>• Brass - keyed different - Schlage C keyway - standard</li> <li>• Drilled 6-Pin, Keyed 5-Pin - standard</li> <li>• Other keying options, including keyed 6-pin, available from factory</li> <li>• Zero bit cylinders will be 6 pin keyed - standard</li> <li>• SFIC mortise housings available</li> <li>• SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard</li> <li>• LFIC mortise housings available</li> <li>• LFIC zero bitted or combined, brass 6-pin sold separately - standard. Schlage C keyway only.</li> <li>• Schlage "L" cam is used standard on Hager mortise locks</li> </ul>
<b>Door Thickness</b>	<ul style="list-style-type: none"> <li>• 1-3/4" - 2-1/2" (45 mm - 64 mm)</li> <li>• Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep</li> </ul>
<b>Escutcheons</b>	1-15/16" x 8" (50 mm x 203 mm)
<b>Exposed Trim</b>	<ul style="list-style-type: none"> <li>• Cast Zinc - Standard</li> <li>• Cast Stainless Steel - Optional on Withnell (WTS) and William (WLS) only</li> </ul>
<b>Finishes</b>	<ul style="list-style-type: none"> <li>• US3, US4, US10B, US26, US26D, US32D*</li> <li>• *US32D look on a cast zinc lever</li> <li>• Withnell or William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order.</li> <li>• US3, US4 and US26 subject to extended lead time</li> </ul>
<b>Functions</b>	Storeroom (F07)

<b>Keyway</b>	Schlage C - Standard, other keyways optional
<b>Latchbolt Type</b>	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
<b>Lever Options</b>	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
<b>Lock Chassis</b>	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
<b>Notes</b>	<ul style="list-style-type: none"><li>• No exposed mounting screws</li><li>• Concealed thru-bolts</li><li>• Body is easily field reversible (shipped LHR by default)</li><li>• Self adjusting case for beveled doors</li></ul>
<b>Options</b>	<ul style="list-style-type: none"><li>• Tactile Warning</li><li>• Lead Lining</li><li>• Split Finish</li><li>• Factory Handing Available (if specified)</li></ul>
<b>Strikes</b>	<ul style="list-style-type: none"><li>• 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike</li><li>• Optional strikes available</li></ul>
<b>Warranty</b>	Lifetime