

3881E - STOREROOM W/ DEADBOLT

3881E



SPECIFICATIONS

Applications	<ul style="list-style-type: none"> • Heavy Duty Commercial • Industrial • Institutional
Backsets	2-3/4" (70mm)
Certifications	<ul style="list-style-type: none"> • ADA Compliant ANSI A117.1 Accessibility Code • UL/cUL Listed for all functions up to 3 hours "A" label single doors • UL10C Positive Pressure Rated • BHMA Certified ANSI A156.13, Series 1000, Grade 1 • ANSI A250.13 Severe Windstorm Compliant (Must specify on PO)
CTC Length	3-5/8" (92mm)
Cylinders/Cores	<ul style="list-style-type: none"> • Brass - keyed different - Schlage C keyway - standard • Drilled 6-Pin, Keyed 5-Pin - standard • Other keying options, including keyed 6-pin, available from factory • Zero bit cylinders will be 6 pin keyed - standard • SFIC mortise housings available • SFIC uncombined or combined, brass 6- or 7-pin cores sold separately - standard • LFIC mortise housings available • LFIC zero bitted or combined, brass 6-pin sold separately - standard. Schlage C keyway only. • Schlage "L" cam is used standard on Hager mortise locks
Deadbolt	1" (25 mm) throw - stainless steel
Door Thickness	<ul style="list-style-type: none"> • 1-3/4" - 2-1/2" (45 mm - 64 mm) • Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep
Escutcheons	1-15/16" x 8" (50 mm x 203 mm)
Exposed Trim	<ul style="list-style-type: none"> • Cast Zinc - Standard • Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only
Finishes	<ul style="list-style-type: none"> • US3, US4, US10B, US26, US26D, US32D* • *US32D look on a cast zinc lever • Withnell or William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order. • US3, US4 and US26 subject to extended lead time

Functions	Storeroom w/Deadbolt
Keyway	Schlage C - Standard, other keyways optional
Latchbolt Type	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
Lever Options	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
Lock Chassis	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
Notes	<ul style="list-style-type: none">• No exposed mounting screws• Concealed thru-bolts• Body is easily field reversible (shipped LHR by default)• Self adjusting case for beveled doors
Options	<ul style="list-style-type: none">• Tactile Warning• Lead Lining• Split Finish• Factory Handing Available (if specified)• Request to Exit (RX)
Strikes	<ul style="list-style-type: none">• 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike• Optional strikes available
Warranty	Lifetime