

3896E - PRIVACY WITH INDICATOR

PRODUCT SPECIFICATIONS

For more information visit www.hagerco.com

- F22	
3896E	
SPECIFICATIONS	
Applications	Heavy Duty CommercialIndustrialInstitutional
Backsets	2–3/4" (70mm)
Certifications	 ADA Compliant ANSI A117.1 Accessibility Code UL/cUL Listed for all functions up to 3 hours "A" label single doors UL10C Positive Pressure Rated BHMA Certified ANSI A156.13, Series 1000, Grade 1
CTC Length	3–5/8" (92mm)
Door Thickness	 1-3/4" - 2" (45 mm - 51 mm) Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep
Escutcheons	1–15/16" x 8" (50 mm x 203 mm)
Exposed Trim	 Cast Zinc - Standard Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only
Finishes	 US3, US4, US10B, US26, US26D, US32D* *US32D look on a cast zinc lever Withnell or William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order. US3, US4 and US26 subject to extended lead time
Functions	Privacy w/Indicator (F22)
Latchbolt Type	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
Lever Options	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
Lock Chassis	4–5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
Notes	 Exterior indicator housing displays "Occupied" or "Vacant" Emergency release on exterior side via supplied key No exposed mounting screws Concealed thru-bolts Body is easily field reversible (shipped LHR by default) Self adjusting case for beyeled doors

• Self adjusting case for beveled doors

Options

- Tactile Warning
- Lead Lining
- Split Finish
- Factory Handing Available (if specified)

Strikes

Warranty

• 1–1/4" x 4–7/8" (32 mm x 124 mm) ASA strike

• Optional strikes available

Lifetime