

3896S - PRIVACY WITH INDICATOR

- F22

3896S



SPECIFICATIONS

Applications	<ul style="list-style-type: none"> • Heavy Duty Commercial • Industrial • Institutional
Backsets	2-3/4" (70mm)
Certifications	<ul style="list-style-type: none"> • ADA Compliant ANSI A117.1 Accessibility Code • UL/cUL Listed for all functions up to 3 hours "A" label single doors • UL10C Positive Pressure Rated • BHMA Certified ANSI A156.13, Series 1000, Grade 1
CTC Length	3-5/8" (92mm)
Door Thickness	<ul style="list-style-type: none"> • 1-3/4" - 2" (45 mm - 51 mm) • Please specify door thickness if greater than 1-3/4" (45 mm) or the door has an offset prep
Exposed Trim	<ul style="list-style-type: none"> • Cast Zinc - Standard • Cast Stainless Steel - Optional for Withnell (WTS) and William (WLS) only
Finishes	<ul style="list-style-type: none"> • US3, US4, US10B, US26, US26D, US32D* • *US32D look on a cast zinc lever • Withnell or William are the only lever options available in both zinc and stainless steel. For stainless steel, reference Withnell (WTS) or William (WLS) at the time of order. • US3, US4 and US26 subject to extended lead time
Functions	Privacy w/ Indicator (F22)
Latchbolt Type	3/4" (19 mm) throw with anti-friction tongue, all stainless steel
Lever Options	Archer, August, Charles, Johnston, Joshua, Louis, Warren, William and Withnell
Lock Chassis	4-5/16" x 6" x 1" (110 mm x 152 mm x 25 mm)
Notes	<ul style="list-style-type: none"> • Exterior indicator housing displays "Occupied" or "Vacant" • Emergency release on exterior side via supplied key • No exposed mounting screws • Concealed thru-bolts • Body is easily field reversible (shipped LHR by default) • Self adjusting case for beveled doors

Options

- Tactile Warning
- Lead Lining
- Split Finish
- Factory Handing Available (if specified)
- ADA Thumbturn

Rose Diameter

2-7/16" (62mm)

Strikes

- 1-1/4" x 4-7/8" (32 mm x 124 mm) ASA strike
- Optional strikes available

Warranty

Lifetime