

## **PRODUCT SPECIFICATIONS**

For more information visit www.hagerco.com

## 9614RS

9614RS



## **SPECIFICATIONS**

**Applications** • Commercial

• Healthcare

Hospitality

Office

• Residential

Certifications • Meets performance requirements ANSI/BHMA A156.14 (Grade 1) for sliding doors

by exceeding 100,000 cycles

• Type D02411-60

Included Features 
• Track is extruded aluminum with "V" shaped rails

• Grooved fascia

• Optional soft-close (1–269–8651) for doors up to 150 lbs.

**Length Options** 48", 60", 72", & 96"

**Maximum Door Thickness** Door thickness 1–3/8"

**Maximum Door Weight** Door weight up to 60 lbs. per door with single wheel hanger

Notes • The 9614RS is the equivalent of previous By-Pass sets 9614 and 9683

 $\bullet \quad \mathsf{IMPORTANT:} \, \mathsf{The} \, \mathsf{components} \, \mathsf{between} \, \mathsf{new} \, \mathsf{and} \, \mathsf{previous} \, \mathsf{versions} \, \mathsf{are} \, \mathsf{NON-}$ 

INTERCHANGEABLE

Options • Aluminum track with fascia

• (4)1-wheel hangers

• (2) Flush cup pulls

• (1) Floor channel door guide

• Parts bag