



C'SINK FOR 1/4-20 FLAT HEAD MACHINE SCREW (2 PLACES)
 A = LEFT HAND REVERSE BEVEL
 B = RIGHT HAND REVERSE BEVEL

$\phi 9/32"$ (2 PLACES)
 A = LEFT HAND REVERSE BEVEL
 B = RIGHT HAND REVERSE BEVEL

ϕ OF EXIT DEVICE CASE & RAIL

OUTSIDE SURFACE OF DOOR

"ET" CONTROL

$\phi 1 1/4"$
 THIS SIDE OF DOOR ONLY
 (NOT REQUIRED FOR 710-4 & 740-4)

41" TO FINISHED FLOOR

SEE NOTE 2

SECTION A-A
 SCALE 1:2

RIGHT HAND REVERSE BEVEL SHOWN

NOTES:

1. FOR ADDITIONAL DOOR PREPARATIONS:
 SEE INSIDE TRIM TEMPLATE #4312 FOR 8400 CONCEALED VERTICAL ROD DEVICE
 SEE INSIDE TRIM TEMPLATE #4447 FOR 12-MD8400 CONCEALED VERTICAL ROD DEVICE
 SEE INSIDE TRIM TEMPLATE #4445 FOR MD8600 & 12-MD8600 CONCEALED VERTICAL ROD DEVICE
2. FOR REFERENCE PURPOSES ONLY: ϕ OF LEVER HANDLE IS 37-3/4" FROM FINISHED FLOOR.
3. SEE TEMPLATE #4571 FOR ELECTROLYNX DETAILS WHEN NEEDED.

SARGENT Manufacturing Company 100 Sargent Drive New Haven, CT 06511	
TEMPLATE: FOR 700-4 "ET" CONTROL FOR USE WITH MD8600, 12-MD8600, MD8400, AND 12-MD8400 CONCEALED VERTICAL ROD EXIT DEVICES	RELEASE DATE 23 JAN 2018 TEMPLATE NO. 4448 J