

LEED® Statement for CRL Glazing Tapes

Thank you for your inquiry concerning LEED®'s (Leadership in Energy and Environmental Design).

The following information is designed to assist you in obtaining LEED Certification Credits for a building project, organized under the appropriate sections for the sealants, adhesives, and tapes we supply.

Section MR (Materials and Resources) This credit relates to products manufactured within 500 miles of the building site location. The manufacturing site for our 980, 740 Series Vinyl Foam Glazing Tapes, and All Purpose Mirror Mounting Foam Tapes listed below is San Antonio, TX 78218, the V2100 Thermalbond Tape is Granville, NY 12832, and the manufacturing site for our GT Series Butyl Tapes is Evansville, IN 47711. Confirm your site is within a 500 mile radius of the manufacturing site.

Section EQ (Indoor Environmental Air Quality) CRL Tape VOC values fall below the applicable VOC limit listed within this credit. This limit is 250 g/L (grams/liter) and is set by the South Coast Air Quality Management District (SCAQMD) Rule #1168 requirements and the Bay Area Air Quality Management District Regulation 9 (BAAQMD) Rule 51 requirements.

Tape

980 Series Vinyl Foam Glazing Tape – Adhesive Two Sides	<5 g/L
740 Series Vinyl Foam Glazing Tape – Adhesive One Side	<5 g/L
All Purpose Mirror Mount Foam Tape – Adhesive Two Sides	<5 g/L
V2100 Thermalbond™ Structural Glazing Spacer Tape	<6.5 g/L
GT Series Butyl Architectural Tape	0 g/L

Further LEED® information is available on the U.S. Green Building Council web site at usgbc.org

Trademark

LEED® is a registered trademark of the U.S. Green Building Council.